



QDD25P

Electric Tractor 2.5t

EP EQUIPMENT CO.,LTD
www.ep-ep.com

Electric tractor 2.5t QDD25P

Distinguishing mark			
1.1	Manufacturer		EP
1.2	Model designation		QDD25P
1.3	Drive unit		Electrical
1.4	Operator type		Standing
1.5	rated capacity	Q	kg 450
	Rated drawbar pull		kg 2000
1.9	Wheelbase	y	mm 1055
Weight			
2.1	Service weight (include battery)		kg 750
2.2	Axle loading, laden Driving/loading		kg 640/560
2.3	Axle loading, unladen Driving/loading		kg 450/300
Types,Chassis			
3.1	Tyre type driving wheels/Loading wheels		solid rubber
3.2	Tyre size, driving wheels (diameter×width)	mm	4.00-8
3.3	Tyre size, steering wheels (diameter×width)	mm	15x4.5
3.5	Wheels, number driving/loading (x=drive wheels)	mm	1/2x
3.7	Track width, rear, loading side	b ₁₁	mm 664
Dimensions			
4.7	Height of overhead, No ladder	h ₆	mm 1265
	Height of overhead, Ladder with 3 stairs		mm 1940
	Height of overhead, Ladder with 5 stairs		mm 2480
4.12	Tow coupling height	h ₁₀	mm 320
4.13	Loading height, unladen	h ₁₁	mm 590
4.16	Length of loading surface	l ₃	mm 1300
4.18	Width of loading surface	b ₉	mm 740
4.19	Overall length, No ladder	l ₁	mm 2190
	Overall length, Ladder with 3 stairs		mm 2300
	Overall length, Ladder with 5 stairs		mm 2400
4.21	Overall width	b ₁ /b ₂	mm 780
4.32	Ground clearance, center of wheelbase	m ₂	mm 74
4.35	turning radius	Wa	mm 1385
Performance data			
5.1	Travel speed, laden/ unladen	km/ h	7/7
5.5	Drawbar pull, laden/unladen	N	640
5.6	Max. drawbar pull, laden/unladen	N	2500
5.8	Max. gradeability, laden/unladen	%	5/20
5.10.1	Service brake type		hydraulic+Mechanical
5.10.2	Park brake type		hydraulic+Mechanical
Electric-engine			
6.1	Drive motor rating S2 60 min	kW	3
6.3	The maximum allowed size battery	mm	/
6.4	Battery voltage/nominal capacity K5		48/200
6.5	Battery weight	kg	200
Addition data			
8.4	Sound pressure level at the driver's ear	dB (A)	70
8.5	Traction pin type	dB (A)	Bolt type

- 1.The parameters in the table are of the standard model. For more information, please contact us.
- 2.The parameters are subject to change without notice.

