

1.-1

pallet truck/Standard

Model		CBY20-II		CBY25-II		CBY30-II	
Capacity	kg	2000		2500		3000	
Overall fork width	mm	450/520/540/685					
Overall fork length	mm	800/900/1000/1100/1150/1220					
Fork width	mm	160					
Lowered fork height	mm	85	75	85	75	85	75
Lifting height	mm	≥110					
Steering wheel size	mm	180*50					
Loading wheel size(single)	mm	Φ80×93	Φ74×93	Φ80×93	Φ74×93	Φ80×93	Φ74×93
Loading wheel size(tandem)	mm	Φ80×70	Φ74×70	Φ80×70	Φ74×70	Φ80×70	Φ74×70



CBY-II



CBY-III

Model		CBY20-III	CBY25-III	CBY30-III
Load capacity	Q (kg)	2000	2500	3000
Load centre distance	c(mm)	500		
Net weight	kg	70-80		
Steering wheel	mm	Φ180*50		
Loading wheel	mm	Φ80*70/Φ74*70		
Lifting height	mm	200/190		
Height of the tiller in drive position min/max	mm	1234/1224		
Lowered height	mm	85/75		
Overall length	mm	1534/1604		
Fork dimensions	s/e/l	54/160/1150		
Distance between fork-arms	mm	550/685		
Aisle width for pallets 1000X1200 crossways	mm	1733/1803		
Aisle width for pallets 800X1200 lengthways	mm	1783/1803		
Turning radius	mm	1249/1319		

